



NOTES:

1. VIEWING ANGLE: 6:00 O' CLOCK
2. DISPLAY MODE: POSITIVE/REFLECTIVE/TN TYPE
3. DRIVING VOLTAGE: 3.0V, DUTY:1/8, BIAS:1/3, FREQUENCY:64Hz
4. OPERATING TEMP. : 0° C TO 50° C
5. STORAGE TEMP. : -10° C TO 60° C
6. CONNECTOR: PIN TYPE
7. SOME CROSSING IN THE VIEW

6									
5	MODIFY BIAS	11/10-07	Y. L. F						
4	MODIFY FIGURE	18/07-07	Y. L. F						
3	MODIFY LOGIC	16/07-07	Y. L. F						
2	MODIFY LOGIC	11/07-07	X. W. D	DESIGN BY	F. C	03/07-07			
1	MODIFY LOGIC	06/07-07	G. W. H	CHECKED BY					
VER.	MODIFY CONTENTS	DATE	DESIGN	APP	BY				
				PART NO.	GD-4935P		TOLERANCES UNLESS OTHERWISE STATED X ± 0.20 XX ± 0.10 ANGLES $\pm 1^{\circ}$		APPLICATION:
				DESIGN BY	F. C 03/07-07		ALL DIMENSIONS IN MM UNLESS OTHERWISE STATED		<input type="checkbox"/> Instrument <input type="checkbox"/> Audio Equipment <input type="checkbox"/> Watch/Clock <input type="checkbox"/> Telephone <input type="checkbox"/> Automobile <input type="checkbox"/> Other <input type="checkbox"/> Home Appliances <input type="checkbox"/> Air-condition
				CUSTOMER:	S-TEK		SAMPLE: <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No		SHEET 1 OF 2
				COMPOSE TYPE:	<input type="checkbox"/> HOLE <input type="checkbox"/> POSITION MM <input type="checkbox"/> HOLE <input type="checkbox"/> POSITION MM				

